

COLOUR TEMPERATURE	adjustable from 2700K to 6500K in 100K steps
LIGHT INTENSITY	dimnable 0 to 100
TLCI INDEX	98 at 3200K and 96 at 5600K
OUTPUT FREQUENCY	flicker free up to 2000 fps
DIMENSIONS	380x308x68mm / 15"x12"x2.7" panel 495x395x68mm / 19.5"x15.5"x2.7" panel+yoke
WEIGHT	4.2kgs / 9 lbs panel 4.7kgs / 10 lbs panel + yoke
POWER DRAW	100 W / 0.91 Amps at 110 VAC
POWER SUPPLY	12-35V DC via XLR3 V-Lock or Gold mount battery plate 90-264V AC 50/60Hz
PHOTOMETRICS	2150 lux / 200 fc at 3m / 9.8 feet 585 lux / 54 fc at 6m / 20 feet
BEAM ANGLE	30° (tunable with optics diffusers)
LED RATED LIFE	more than 50.000 hours
COOLING	no-noise, fan-free passive cooling
PROTECTION	IP54 rain and dust proof, indoor or outdoor use
CONSTRUCTION & FINISH	Made of black powdercoated extruded and sheet aluminum
VELVET LED TECHNOLOGY	selected BIN high-power LED + VELVET custom optics + CPU software control
ACCESSORIES	Quarter, half and full hard diffusion, foldable Snapbag diffuser kit, foldable 20°, 40° or 60° Snapgrids, removable barndoors, AC power adapter, V-Lock or Gold Mount battery mounts, remote control, Cordura carrying bag, hard case.