

COLOUR TEMPERATURE	adjustable from 2700K to 6500K in 100K steps
LIGHT INTENSITY	dimnable 0 to 100
OUTPUT FREQUENCY	98 at 3200K and 96 at 5600K
FLICKER FREE	flicker-free up to 2000 fps
DIMENSIONS	690x308x68mm / 27"x12"x2.7" panel 815x430x68mm / 32"x17"x2.7" panel + yoke
WEIGHT	7 kgs / 15,5 lbs panel 7.6kgs / 16.7 lbs panel + yoke
POWER DRAW	190W
POWER SUPPLY	24-35V DC via XLR3 V-Lock or Gold mount battery plate 90-264V AC 50/60Hz
PHOTOMETRICS	4950 lux / 460 fc at 3m / 9.8 feet 1330 lux / 124 fc at 6m / 20 feet
BEAM ANGLE	30° (tunable with optics diffusers)
LED RATED LIFE	more than 50,000 hours
COOLING	no-noise, fan-free passive cooling
PROTECTION	IP54 rain and dust proof, indoor or outdoor use
CONSTRUCTION & FINISH	Made of black powdercoated extruded and sheet aluminum
VELVET LED TECHNOLOGY	selected BIN high-power LED + VELVET custom optics + CPU software control
ACCESSORIES	Quarter, half and full hard diffusion, foldable Snapbag diffuser kit, foldable 20°, 40° or 60° Snapgrids, removable barndoors, AC power adapter, V-Lock or Gold Mount battery mounts, remote control, Cordura carrying bag, hard case