

COLOUR TEMPERATURE	adjustable from 2700K to 6500K in 100K steps
LIGHT INTENSITY	dimnable 0 to 100/ flicker-free up to 2000 fps
TLCI INDEX	98 at 3200K and 96 at 5600K
DIMENSIONS	690x620x68mm / 27"x24.5"x2.7" panel 770x750x125mm / 30"x29.5"x5" panel + yoke + PSU
WEIGHT	14 kg / 31 lbs panel 16 kg / 35.3 lbs panel + yoke 20 kg / 44 lbs panel + yoke + PSU
POWER DRAW	340W (12.1 Amps at 28 VDC – 0.7 Amps at 230VAC)
POWER SUPPLY	26-28V DC 90-264V AC 50/60Hz
PHOTOMETRICS	10000 lux / 929 fc at 3m / 9.8 feet 2260 lux / 247 fc at 6m / 20 feet
BEAM ANGLE	30° (tunable with optics diffusers)
LED RATED LIFE	more than 50,000 hours
COOLING	no-noise, fan-free passive cooling
PROTECTION	IP51 dust proof, indoor or outdoor use
CONSTRUCTION & FINISH	Made of black powdercoated extruded and sheet aluminum
VELVET LED TECHNOLOGY	selected BIN high-power LED + VELVET custom optics + CPU software control
ACCESSORIES	AC power supply, foldable 20°, 40° or 60° Snapgrids, foldable Snapbag softbox, spacelight cylinder, removable barn doors, remote control, hard case